

Data Sheet

Model: TLCF12/125

Top Loading Chamber Furnaces



INTRODUCTION

TLCF12 Top Loading Chamber Furnaces are suited to application which involve heavy loads, where samples are contained in tall crucibles, or where there is a danger of spillage onto the base of the chamber and is available in various capacities ranging from 5 litres to 125 litres in standard versions. Other chamber capacities/volumes are offered in custom-built models.

The **TLCF12/125** chamber furnace has a 125-liter capacity.

SPECIFICATIONS

Maximum Temperature: 1200°C

Maximum Continuous Temperature: 1150°C



TLCF12/125

- | Floor mounted design
- | Chamber dimensions (mm): 620 x 450 x 450 (H x W x D)
- | Energy efficient, high quality, low thermal mass brick insulation
- | These heating elements are robust cast refractory panels mounted on all sides
- | Type 'R' thermocouple
- | A lever allows the operator to open and close top opening door safely and conveniently
- | High end Microprocessor PID controller
- | Exhaust port to assist fumes removal is fitted to the furnace door
- | **External Dimensions (mm):** 1175 x 950 x 950 (H x W x D)
(Indicative)
[Dimensions with door closed]
- | Supply / Power: 400V– 3 Phase – 18.0 kW

OPTIONS

- | Independent Over-temperature protection system
- | Multi segment, multi program storage controllers
- | Monitoring probes

SYLAB SCIENTIFIC PVT. LTD.

Formerly SYLAB PVT. LTD.

Ground Floor, B-50, Industrial Estate, Sanath Nagar, Hyderabad-500018. INDIA,
Phone: +91 40 67216376 E-mail: sales@sylabscientific.com Website: www.sylabscientific.com