

Data Sheet

Model: TSHvc12/75/600-LV

1200 °C Maximum Temperature,
Single Zone Horizontal Vacuum Tube Furnace with
Low Vacuum System



INTRODUCTION

The TSHvc12-LV is a Floor mounted tube furnace ideal for most general laboratory low vacuum thermal processing applications.

The TSHvc12/75 Single Zone Tube furnace includes a work tube with internal tube diameter of 75 mm as the vacuum chamber.

TSHvc12/75/600-LV comes with a heated zone length of 600 mm.

SPECIFICATIONS

Maximum Temperature: 1200 °C

Maximum Continuous Temperature: 1150 °C

- | The furnace design incorporates an integral elemental tube.
- | Protective outer mesh covers for improved operator safety.
- | High grade resistance wire wound heating elements.
- | Energy efficient, high quality, low thermal mass insulation.
- | Temperature Sensor: 'N' Type thermocouple.
- | High end Microprocessor PID controller.
- | Over temperature protection controller.

OTHERS

The vacuum furnace system comprising of the following is included:

- | Ceramic work tube.
- | Vacuum ready end flange gas tight seals.
- | Thermal radiation plugs.
- | Rotary pump-two stage sliding vane type for ultimate vacuum level up to 1×10^{-3} mbar with clean empty work tube.
- | Pirani gauge with wide range of vacuum level.
- | Flowmeter for control of gas throughput. Vacuum tight valve.
- | Gas in/outlet valve.



*Illustrative image only

TSHvc12/75/600-LV

Furnace External Dimensions (mm): H x W x D
(Nominal) TSHvc12/75/600-LV 1450 x 1850 x 700

Net weight of the total instruments approximately: 195 kg

Supply: 230V– 1 Phase – 50/60Hz

Energy rating: 4.0 kW

OPTIONS

- | Multi segment, multi program storage controller
- | Semi-automatic or fully automatic vacuum/heating cycles

SYLAB SCIENTIFIC PVT. LTD.

Formerly SYLAB PVT. LTD.

Ground Floor, B-50, Industrial Estate, Sanath Nagar, Hyderabad-500018. INDIA,
Phone: +91 40 67216376 E-mail: sales@sylabscientific.com Website: www.sylabscientific.com